Roof Flashings

Panel Profile Type	Minimum Pitch 7 °	Minimum Pitch 3 °
STS Panels®	25mm Seam	38mm Seam
TSS Panels®		25mm Seam

*Circle to select the panel profile option these flashings relate to.

Standard	Drawing Ref.	Girth	Length mm	Quantity
Eaves				
Ridge				
Apex				
Verge				
Abutment				
Chase				
Valley				

Custom	Drawing Ref.	Girth	Length mm	Quantity

Materials

0.6mm Greencoat PLX Pural BT
0.7mm Pre Coated Aluminium
0.5mm Roofinox Stainless Steel
0.5mm Corten Steel
0.6mm Aurubis Copper
0.8mm Nedzink
0.8mm ZM Silesia
0.8mm Zintek

** If planning to use STS Panels®*

The Zinc Options Above Are Only Available in TSS Panels® (Traditional Standing Seam)

Note:

Please provide related drawings. Clearly showing all dimensions. Angles & the finish side.

Ensure the person installing, Checks & confirms all items, as correct before ordering.

We can not be held responsible, for the accuracy of schedules. Customers must thoroughly, check order details to avoid, production errors & additional related costs. Related to correcting any errors.

MERLINMETALS®

Customer Name	Project Ref.	Sheet No.	Date	Metal Finish