

# Wall Flashings

Panel Profile Type	Minimum Pitch 7 °	Minimum Pitch 3 °
STS Panels®	25mm Seam	38mm Seam
TSS Panels®		25mm Seam

\*Circle to select the panel profile option these flashings relate to.

Standard	Drawing Ref.	Girth	Length mm	Quantity
Ventilated Cill				
Cill				
Head				
Wall Abutment				
Box Abutment				
Base 1				
Base 2				
Internal Corner				
External Corner				
External Coulisseau				
Reveal 1				
Reveal 2				
Reveal 3				

Custom	Drawing Ref.	Girth	Length mm	Quantity

# Materials

- 0.6mm Greencoat PLX Pural BT
- 0.7mm Pre Coated Aluminium
- 0.5mm Roofinox Stainless Steel
- 0.5mm Corten Steel
- 0.6mm Aurubis Copper
- 0.8mm Nedzink
- 0.8mm ZM Silesia
- 0.8mm Zintek

*\* If planning to use STS Panels®  
The Zinc Options Above Are Only Available in  
TSS Panels® (Traditional Standing Seam)*

### Note:

Please provide related drawings. Clearly showing all dimensions. Angles & the finish side.

Ensure the person installing, Checks & confirms all items, as correct before ordering.

We can not be held responsible, for the accuracy of schedules. Customers must thoroughly, check order details to avoid, production errors & additional related costs. Related to correcting any errors.



Customer Name	Project Ref.	Sheet No.	Date	Metal Finish